

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-156360

(43)Date of publication of application : 15.06.1999

(51)Int.Cl.

C02F 1/44

B01D 65/02

C02F 3/12

(21)Application number : 09-321823

(71)Applicant : KUBOTA CORP

(22)Date of filing : 25.11.1997

(72)Inventor : ITO HAJIME

OKUMURA TOSHIKAZU

TOKUSHIMA KANJI

OKADA KOICHI

HONDA KAZUYUKI

(54) METHOD FOR OPERATION OF WATER TREATMENT PLANT

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a method for operation of a water treatment plant wherein fouling hardly occurs even when the filtration quantity of a membrane separation apparatus is increased.

SOLUTION: Filtration is caused through a membrane surface by making the suction pressure of a suction pump 29 act on a permeated water channel of a membrane separation apparatus. When membrane permeated water flowing into the permeated water channel after permeating a membrane surface is discharged through a permeated water discharging pipe 28, a specific flow quantity of aerated air which is set according to the quantity of a discharged water flow rate of the membrane permeated water is ejected through an aeration device 21, and a membrane surface of the upward membrane separation apparatus 22 is washed.

